



INSTRUMENTATION STOCKING PROGRAM

PRESSURE • TEMPERATURE • TRANSMITTERS • VALVES • ACCESSORIES

1,200+ stock configurations ready to ship in 2-10 business days.

Direct crossovers available for many common competitors' pressure and temperature products

GET THE INSTRUMENTATION YOU NEED - FAST				COLESCO - WIKA QUICK SHIP PROGRAM			
MECHANICAL PRESSURE COMMERCIAL, INDUSTRIAL & PROCESS GAUGES				MECHANICAL TEMPERATURE BIMETAL THERMOMETERS & THERMOWELLS			
Type	Size	Range (PSI)	Connection / Material	Type	Model / Size	Range / Scale	Connection / Design
Commercial / regulator	1.5-4 in.	-14.7 vacuum to 4,000	1/8-1/4 NPT; brass; dry/filled	Bimetal thermometer	TG51/TG53; 3 & 5 in.	-40°F to 550°F; °F or °F/°C	Back/adjustable; 2.5-12 in.; 304 SS
Industrial / hydraulic	2-4.5 in.	-14.7 vacuum to 15,000	1/4-1/2 NPT; brass/316L SS				
Process / all-stainless	2-4.5 in.	-14.7 vacuum to 10,000	1/4-1/2 NPT; 316L SS	Thermowell	TW15	Application matched	Straight/stepped/tapered; 304/316 SS
Low / differential	2.5-6 in.	-3.6 to 10; to 3.6 psid	Capsule, piston or diaphragm				
Digital	4 in.	0 to 300	1/4 NPT; 316L SS; ±0.1%				
ELECTRICAL PRESSURE TRANSMITTERS, SWITCHES & INDICATION				ELECTRICAL TEMPERATURE HEAD- & RAIL-MOUNT TRANSMITTERS			
Type	Range	Output	Connection / Material	Type	Model	Supply / Design	Protocol / Setting
General purpose	1 psi/100 inWC to 10,000 psi	4-20 mA; 0-10 V; 1-5 V	DIN/cable; NPT; 316L SS	Temperature transmitter	T15	8-35 V DC; head/rail	4-20 mA; Pt100 0-150°C
				Temperature transmitter	T16	10-35 V DC; head/rail	4-20 mA; Type K 0-600°C
Flush diaphragm	60-2,000 psi	4-20 mA, 2-wire	G1/2B or G1B; 316L SS	Digital transmitter	T32	8-35 V DC; head/rail	HART; 4-20 mA; Pt100
Hazardous area	Compound to 10,000 psi	4-20 mA or 1-5 V	Conduit; 1/4 or 1/2 NPT				
Programmable switch	Up to 3,000 psi	Switching + analog output	M12; 1/4 NPT; LED display				
INSTRUMENT VALVES ISOLATION, BLOCK & BLEED & MANIFOLDS				PRESSURE ACCESSORIES PROTECTION, ISOLATION & INSTALLATION			
Type	Model / Design	Connections	Body / Pressure	Type	Model / Style	Rating	Connection / Material
1-way valve	IV10	1/4, 3/8 or 1/2 NPT	316/316L SS; 6,000/10,000 psi	Overpressure protector	910.13	Up to 6,000 psi	1/2 NPT; 316 SS
1-way multiport	IV11	1/2 instrument; 1/2-3/4 process	316/316L SS; 6,000/10,000 psi	Cocks / needle valves	910.10 / 910.11	Up to 6,000 psi	1/4 NPT; brass/CS/316 SS
				Snubbers	910.12	Up to 15,000 psi	1/4-1/2 NPT; brass/316 SS
2-way block & bleed	IV202; in-line	1/2 NPT; 1/4 vent	316/316L SS; 6,000 psi	Siphons / cooling	910.15 / .24 / .32	Design dependent	1/4-1/2 NPT; steel/316 SS
5-way manifold	IV516; angled	IEC 61518-B / 1/2 NPT	316/316L SS; 6,000 psi	Covers / contacts	910.18 / CP3000 / CP4000	Application dependent	PVC; magnetic/inductive
NEED HELP SELECTING THE RIGHT WIKA CONFIGURATION?				513-489-1122 sales@colesco.com			

Product availability and exact configuration depend on application requirements.

Contact Colesco to confirm selection, crossover part numbers, price, current stock and delivery.